

# Build Logs



Before reading this page, it is highly recommended you read the [builds](#) page.

- [What is the Build Log?](#)
- [What Information is Logged?](#)
  - [Actions](#)
  - [Repository Syncing](#)
  - [Workspace Syncing](#)
  - [Artifact Registration](#)
- [The Build Log Page](#)
- [I can't see my build log!](#)

## What is the Build Log?

As the build runs and each stage executes, build information is logged to a file in the build's workspace.

## What Information is Logged?

### Actions

Every [action](#) that is executed during a build will write its output to the build log. The build log is normally the first port of call to check why a build action has failed. Some actions allow you to set the debugging level so if an action is failing and it is hard to determine why, then check if you can increase the action's log level.

### Repository Syncing

Repository syncing will list every file that is pulled from your repository and sent to the agent workspace every time a stage is executed. This information can be extremely useful when determining if certain files are being copied over to the workspace correctly.

Repository syncing is enabled or disabled on a stage by stage basis. By default repository syncing is turned off for every stage. Logging every file that is pulled from the repository and sent to the workspace is extremely taxing and it will slow down the performance on the agents. It is recommended that repository sync logging should only be enabled while debugging.

Repository syncing can be enabled and disabled for a [stage](#) by editing a stage in the **Stages section** of the [Configuration Wizard](#).

### Workspace Syncing

Workspace syncing will list every file that is copied from the Server's Workspace to the Agent's Workspace and vice versa. Like repository syncing, this information can be used to check that your [Workspace Rules](#) are configured correctly and that all of your files are being copied between the server and agent.

Workspace syncing is enabled or disabled on a stage by stage basis. By default workspace syncing is turned off for every stage. Logging every file that is sent between the server and agent is a large performance hit so it is recommended that workspace sync logging should only be enabled while debugging.

Workspace syncing can be enabled and disabled for a [stage](#) by editing a stage in the **Stages section** of the [Configuration Wizard](#).

### Artifact Registration

Artifact registration lists every file that is registered as an artifact at the end of a stage. This can be useful if a registered artifact is not there at the end of a build.

Artifact registration is enabled or disabled on a stage by stage basis. By default artifact registration is turned off for every stage. Logging every file that is registered can be a large performance hit so it is recommended that artifact registration should only be enabled while debugging.

Workspace syncing can be enabled and disabled for a [stage](#) by editing a stage in the **Stages section** of the [Configuration Wizard](#).

## The Build Log Page

The Build Log page can be found in Continua by navigating to a particular build and clicking the **Log** tab. The build log that is displayed shows every action that was executed during the build, workspace syncing, repository syncing and artifact registration.

The first tier nodes of the log are the stage that were run and the second tier nodes are the actions that were executed. Clicking on the action will give you either the actions it executed or the actual output of the action. You will get the entire output of the action and the full path to the working directory, executable and all the parameters passed to it. Alternatively you can download the entire log as a text file by clicking **[Download As Plain Text]**.

Dev Project

Home > Dev Project > CI > release > 1.0.0.46 > Log

Dev Project : release - Build : 1.0.0.46

Build

Duration: 8s 964ms

Status: Stage Completed

Agent: lancer

test

Duration: 32s 617ms

Status: Stage Failed

Agent: lancer

Build - 1.0.0.46

DETAILS LOG UNIT TESTS (242) ARTIFACTS (2) CHANGES (0) REPORTS ISSUES (0) TIMELINE COMMENTS (0)

Build Log [Download As Plain Text]

Name	Started	Finished	Duration	Status
Build	14:21	14:21	8 seconds	Stage completed
Server To Agent Workspace Sync	14:21	14:21	74 milliseconds	Success
Create Directory [\${Workspace}\output\tests]	14:21	14:21	0 milliseconds	Success
Copy [I:\continua\build\debug]	14:21	14:21	336 milliseconds	Success
Agent To Server Workspace Sync	14:21	14:21	6 seconds	Success
ArtifactsRegistration	14:21	14:21	26 milliseconds	Success
test	14:21	14:22	32 seconds	Stage failed
Server To Agent Workspace Sync	14:21	14:21	4 seconds	Success
Started syncing files from the server [localhost] to the agent [LANCER]				
Finished syncing files from the server [localhost] to the agent [LANCER].				
NUnit [I:\continua\Source\Continua.Tests\continua.tests.csproj]	14:21	14:21	4 seconds	Failure
NUnit [I:\output\tests\continua.common.tests.dll]				Skipped
Agent To Server Workspace Sync	14:21	14:22	23 seconds	Success
ArtifactsRegistration	14:22	14:22	10 milliseconds	Success
Started registering artifacts				
Finished registering artifacts				

### I can't see my build log!

Logs can be deleted as part of a [Cleanup Policy](#). Each cleanup policy can be set to specifically delete build logs which means that any affected builds will lose their logs. Once a log has been removed it cannot be recovered.

Alternatively, a log will not have been generated if the build was cancelled before it was sent to an agent.

Dev Project

Home > Dev Project > CI > testHg > #30 > Log

Dev Project : testHg - Build : #30

Build

Duration:

Status: Stage Not Run

Build - #30

DETAILS LOG UNIT TESTS (0) ARTIFACTS (0) CHANGES (1) REPORTS ISSUES (0) TIMELINE COMMENTS (0)

Build Log

No log file was found. It may have been removed by the build cleanup process, or it may not have been created if the build was stopped during initialisation.