

# Maven Action



The Maven action in Continua is a wrapper around the mvn command line. If you're having trouble using the Maven action, please refer to the [Command Line Reference](#) or [reference articles](#).

Apache Maven is a build automation tool used primarily for Java projects but can be used to build and manage projects written in C#, Ruby, Scala, and other languages.

## Maven

Maven Action

Maven

Settings

Paths

Logging and Failure

System Properties

Options

Environment

Comments

Required Field

Name

Maven []

☒

Enabled

Project Folder

\$Source.MyRepository\$\app\

The start directory for Maven.

Phases and Goals

clean dependency:copy-dependencies package

The build lifecycle phases and goals that Maven should run.

Using

Maven.Runtime.Default

Validate

Save

Cancel

Help

### Name

A name for this action (this will appear within the stage action list).

### Enabled

An action which is not enabled is effectively skipped when executing the given stage.

### Project Folder

The start or working directory to run the Maven command line in.

### Phases and Goals

The build lifecycle phases and goals to run

### Using

The Using drop down is populated by any property collector properties whose namespace matches the pattern defined by the Maven action. The pattern for this action is `^Maven\..*`. The default property collector searches the environment path for "mvn.cmd".

If you create a property collector for this action, make sure you select the **Path Finder Plugin** type and give it a name that will match the pattern above in blue. Example names listed [here](#), search the table's Plugin column for "Maven".

For more in-depth explanations on property collectors see [Property Collectors](#).

Alternatively, you can select the **Custom** option from the Using drop down list and specify a path in the resulting input field that will be displayed. Please read [Why it's a good idea to use a property collector](#) before using this option.

## Settings

Maven Action

Maven

Settings

Paths

Logging and Failure

System Properties

Options

Environment

Comments

Build Strategy ID

Required Field

Activate Profiles

Comma-delimited list of profiles to activate. [--activate-profiles]

Projects

Comma-delimited list of specific reactor projects to build instead of all projects. A project can be specified by [groupId]:artifactId or by its relative path. [--projects]

Resume From

Resume reactor from specified project. [--resume-form]

Validate

Save

Cancel

Help

### Build Strategy ID

The id of the build strategy to use. [--builder]

### Activate Profiles

A comma-delimited list of profile-ids of build profiles to activate. [--activate-profiles]

### Projects

Comma-delimited list of specific reactor projects to build instead of all projects. A project can be specified by [groupId]:artifactId or by its relative path. [--projects]

### Resume From

Specif a project name to resume a build from a particular project. [--resume-from]

## Paths

Maven Action

Maven

Settings

Paths

Logging and Failure

System Properties

Options

Environment

Comments

Required Field

Global Settings Path

Alternate path for the global settings files. [--global-settings]

Settings Path

Alternate path for the user settings file. [--settings]

Global Tool Chains Path

Alternate path for the global toolchains file. [--global-toolchains]

User Tool Chains Path

Alternate path for the user toolchains file. [--toolchains]

Validate

Save

Cancel

Help

## Global Settings Path

An alternate path for the global setting file. [--global-settings]

## Settings Path

An alternate path for the user setting file. [--settings]

## Global Tool Chains Path

An alternate path for the global toolchains file. [--global-toolchains]

## User Tool Chains Path

An alternate path for the user toolchains file. [--toolchains]

## Logging and Failure

Maven Action

Maven

Settings

Paths

Logging and Failure

System Properties

Options

Environment

Comments

Required Field

Log Level

Normal

☐

Produce execution error messages. [--errors]

☐

Never fail the build regardless of project result. [--fail-never]

☐

Only fail the build afterwards; allow all non-impacted builds to continue. [--fail-at-end]

☐

Stop at first failure in reactorized builds. [--fail-fast]

Validate

Save

Cancel

Help

## Log Level

Logging verbosity level (Quiet, Errors, Normal, Debug).

The Quiet option only prints a message to the output if there is an error or a problem. [--quiet]

The Debug option will print an overwhelming amount of debugging log messages to the output and is useful if you are attempting to diagnose a difficult problem with a dependency or a classpath. [--debug]

## Produce execution error messages

As described. Useful you need to diagnose an error in a Maven plugin. [--errors]

## Never fail the build regardless of project result

As described. [--fail-never]

## Only fail the build afterwards; allow all non-impacted builds to continue

As described. [--fail-at-end]

## Stop at first failure in reactorized builds

As described. [--fail-fast]

## System Properties

Maven Action

Maven

Settings

Paths

Logging and Failure

System Properties

Options

Environment

Comments

System Properties

Required Field

variable\_name=variable\_value

Specify one name & value pair per line. [--define]

Validate

Save

Cancel

Help

## System Properties

Use this field to define the values of properties to be used in a Maven POM or Plugin. Specify each property as a name and value pair - one per line. [--define]

## Options

Maven Action
Maven
Settings
Paths
Logging and Failure
System Properties
Options
Environment
Comments

Required Field

☐ Use Maven 2 Legacy Local Repository behaviour. i.e. no use of `_remote.repositories`. [`--legacy-local-repository`]
☐ Do not recurse into sub-projects. [`--non-recursive`]
☐ Work offline. [`--offline`]

Snapshots
Default
Whether to update the snapshots or not. [`--update-snapshots` | `--no-snapshots-update`]

Checksums
No checksums

Thread Count
For instance 2.0C, where C is core multiplied. [`--threads`]

Timeout (in seconds)
0
How long to wait for the action to finish running before timing out. Leaving this blank (or zero) will default to 86400 seconds (24 hours).
☐ Treat failure as warning  
Tick to continue build on failure marking the action with a warning status.
☐ Ignore warnings

Validate
Save
Cancel
Help

## Use Maven 2 Legacy Local Repository behaviour. i.e. no use of `_remote.repositories`

As described. [`--legacy-local-repository`]

## Do not recurse into sub-projects

Skip child projects. [`--non-recursive`]

## Work offline

Build the project in offline mode using local files without connecting to remote repositories for updates. [`--offline`]

## Snapshots

Choose **"Update Snapshots"** to force a check for update releases and snapshots on remote repositories. [`--update-snapshots`]

Choose **"No Snapshot Updates"** to suppress checking for update releases and snapshots on remote repositories. [`--no-snapshot-updates`]

Choose **"Default"** to default to the snapshot updating policy set in your environment.

## Checksums

Choose **"Strict Checksums"** to fail the build if the checksums do not match the when downloading artifacts from repositories. [`--strict-checksums`]

Choose **"Lax Checksums"** to cause a warning to be displayed if the checksums do not match the when downloading artifacts from repositories. [`--lax-checksums`]

Choose **"No Checksums"** to default to ignoring checksum mismatches.

## Thread Count

Number of threads Maven should use for parallel builds. Specify the exact number of threads e.g. 4, or a core multiplier e.g. 2C or 1.5C for 2 threads per core or 1.5 threads per core. [`--threads`]

## Timeout (in seconds)

Number of seconds Continua CI should wait before timing out the Maven action and aborting the command line.

## Treat failure as warning

Tick to continue build on failure marking the action with a warning status.

## Ignore warnings

If this is ticked, any warnings logged will not mark the action with a warning status.

## Environment

**Maven Action**

MavenSettingsPathsLogging and FailureSystem PropertiesOptions**Environment**Comments

Environment Variables

variable\_name=variable\_value

Required Field

Specify one name & value pair per line.

☒ Log environment variables

☐ Generate system environment variables

Tick this to set new environment variables prefixed with 'ContinuaCI.' for system objects and variables.

### Environment Variables

Multiple environment variables can be defined - one per line. These are set before the command line is run.

### Log environment variables

If this is ticked, environment variable values are written to the build log.

### Generate system environment variables

Tick this checkbox to set up a list of new environment variables prefixed with 'ContinuaCI.' for all current system expression objects and variables.

### Mask sensitive variable values in system environment variables

This checkbox is visible only if the 'Generate system environment variables' checkbox is ticked.

If this is ticked, the values of any variables marked as sensitive will be masked with \*\*\*\* when setting system environment variables. Clear this to expose the values.