



Here you can link reports to your builds. Any report defined here will appear in the build section under the 'REPORTS' tab. This is especially useful for reports generated as part of the build process. i.e. code coverage reports, unit tests etc.

- [Configuration Reports](#)

**Reports** [\[Create\]](#)

Status	Name	Location	Description	Report Order
No reports were found.				

[← Back](#)
[✔ Complete Wizard](#)
[Continue →](#)

## New/Edit Report

**New Report**

Required Field

**Name**

**Report Filename**  ✔ ?

The location of the main report file.

Enabled

**Description**

**Report Order**

Save
Cancel
Help

### Name

The name Continua CI uses to identify the report. This is displayed on the build report page.

### Report Filename

The location of the **root file** of the report. This is the initial page that will be displayed when viewing the report.

For example, if it is a HTML report then this is usually default.html or index.html.

This field also allows [Variables, Objects & Expressions](#) to be used. This means that you can specify the file location based on the builds workspace.

For example, if your code coverage report was saved in your output folder of the workspace then the path would be \$Workspace\$/Output /codeCoverageReport/index.html

It is recommended that all reports are stored and referenced using the \$Workspace\$ which allows each report to be stored and associated with each individual build. Note that when you refer to \$Workspace\$ that this is referring to the **server's workspace** so make sure that any generated reports are synced back to the server with your [Workspace Rules](#).

### Enabled

Only enabled reports will be displayed on builds.

## Description

Extra information regarding the report. This information is shown when you hover over its report tab in the build.

## Report Order

The order in which the report will be run (relevant in the situation where multiple reports are present).

## Help! My report is missing from the \$Workspace\$ directory

If your report is being generated on an agent but it is missing from the Continua Workspace then the report may not be getting copied from the agent to the server correctly.

This can be checked and edited in the [Workspace Rules](#) for each Stage in the Stages editor. Make sure that all the necessary folders and files have been configured to copy across back to the server.

## Folder Security

All reports that are shown in Continua are accessed using the IIS anonymous user. The files are served up from the ContinuaShare\WS folder, read access must be granted to the IIS anonymous user for this folder.

Access must be granted in different ways depending on which version of IIS Continua is running under. Note that these users belong to the local machine, not the domain. When adding the permissions through explorer, be sure to set the location to the local machine, this is especially important if the machine is on a domain.

- IIS 8 & 7.5: The IIS App Pool that Continua is running under must be granted read access for all report folders. The app pool user is typically 'IIS AppPool\<AppPoolName>'. By default, Continua is configured to use the 'ContinuaCI' App Pool, so the user would be 'IIS AppPool\ContinuaCI'.
- IIS 7: The 'IUSR' local user must be granted read access for all report folders.
- IIS 6: The 'ASPNET' local user must be granted read access for all report folders.