

Start, Stop or Restart Website Action - [IIS 7]

The Start / Stop / Restart Website (IIS 7) action enables you to change the current state of an existing website.

You can choose to start, stop or restart the web site by selected the relevant action in the drop down list.

Server

The screenshot shows a dialog box titled "Start / Stop / Restart Website (IIS 7)" with a close button (X) in the top right corner. The dialog has four tabs: "General", "Runtime", "Server" (which is selected and highlighted in blue), and "Website Options".

Under the "Server" tab, there are two main sections:

- IIS server (IIS 7)**: This section contains two radio buttons. The first is "Use the hostname specified in the global IIS options." and the second is "Provide the hostname of the IIS server." Below the second radio button is a text field labeled "Hostname:". Below the text field is the instruction "Leave blank to connect to the local machine."
- Credentials (IIS 7)**: This section contains two radio buttons. The first is "Use the credentials specified in the global IIS options." and the second is "Provide the credentials to the IIS server." Below the second radio button is a text field labeled "Username:". Below the "Username:" field is the instruction "Leave blank to use the credentials of the logged in user." Below this instruction is a text field labeled "Password:".

At the bottom of the dialog box, there are three buttons: "OK", "Cancel", and "Help".

IIS server

Use the hostname specified in the global IIS options

Provide the hostname of the IIS server

Credentials

Use the credentials specified in the global IIS options

Provide the credentials to the IIS server


Username

Password

Website Options

Start / Stop / Restart Website (IIS 7) ✕

General Runtime Server **Website Options** ⌵

 **Website**

☐ Website index

☒ Website name

Action

OK Cancel Help

Website

Website index

Website name

Action