

Edit XML File Action

This action allows you to modify a value in an XML document. The value to modify is selected using XPath, if the Attribute field is empty the node text will be set.

Edit XML File

General Runtime **Edit XML** MSXML Parser

XML file

☐ XML source file

☒ XML document

ConfigOptions

Edit XML

XPath

/BuildVersion

Attribute (optional)

New value

```
<major>%majorVer%</major>
<minor>%minorVer%</minor>
<build>%buildVer%</build>
```

☒ Treat new value as text (if this is not checked, the new value will be assumed to be xml)

☐ Preserve white space

☐ Insert new value in CDATA

OK Cancel Help

XML File

Specify an XML file or [document](#) to edit.

XPath

Specify the XPath of the node you wish to edit.

Attribute (optional)

If you specify an attribute here then that attribute's value will be set to 'New Value.'

If you do not specify an attribute, then the entire contents of the selected node will be set instead.

New Value

Specify the value to write to the XML file.

MSXML Parser Page

Allows you to set some options to be used when the parser loads the XML. See the [XML Parser Options](#) topic for details.

Preserve Whitespace

This option specifies the default white space handling of the MSXML parser. When set to true, all white space is preserved, regardless of any xml:space attributes specified in the document type definition (DTD). It is equivalent to having an xml:space="preserve" attribute on every element. When Preserve Whitespace is False, the values of any xml:space attributes determine where white space is preserved.