

String Add Breaks Action

The String Add Breaks action enables you to add breaks at specified locations within a string.

Input And Output

The screenshot shows the 'String Add Breaks' dialog box with the 'Input and Output' tab selected. The dialog has a title bar with a close button (X) and a tab bar with four tabs: 'General', 'Runtime', 'Input and Output' (active), and 'Break Options'. The 'Input' section has a label '% Input' and a text field. Below it, there are two radio buttons: 'From variable' (selected) and 'Specify value'. The 'From variable' option has a dropdown menu showing 'L_File'. The 'Specify value' option has an empty text field. The 'Output' section has a label '% Output' and a text field. Below it, there are two radio buttons: 'Apply to existing value' (selected) and 'Specify output variable'. The 'Specify output variable' option has an empty text field. At the bottom, there are three buttons: 'OK', 'Cancel', and 'Help'.

Input

From variable

Add breaks to an existing string.

Specify value

Add breaks to a new string.

Output

Apply to existing variable

Output the change to the original variable.

Specify output variable

Choose the variable to output the change to.

Break Options

String Add Breaks

General

Runtime

Input and Output

Break Options

 Break style

☒ Carriage return and line feed

☐ HTML line break

 Insertion options

☐ Letter count

☒ Word count

☐ After a string

☐ Before a string

☐ Instead of string

Count

20

Search string

☒ Case sensitive

OK

Cancel

Help

Break Style

This action can insert either a Carriage Return and Line Feed, which is the default for Windows operating systems, or a HTML line break.

Carriage return and line feed

This action will set the cursor to the start of a new line.

HTML line break

Insertion options

Letter Count

Inserts a break after a set number of characters.

Word Count

Inserts a break after a set number of words.

Before a string

After a string

Inserts a break before or after the search string.

Instead of string

Replaces the search string with a break

Search string

Specify a string to be acted on.

Case sensitive

Toggles the importance of capital letters in the search string. eg. "string" is the same as "STRING" if box is unchecked.

Scripting Info

The Action properties available are :

property InputString : string;// The input string, if not using a variable

property OutputVariable: string;// The Output Variable name

property ApplyToInput : boolean;// Apply the changes to the input variable, only valid if using an input variable

property UsingInputVariable : boolean;// True if using an input variable, not input string

property InputVariable : string;// Input variable name

property UseHtmlBreak : boolean;// True to Use Html Break, False to use CRLF

property BreakOnLetterCount: boolean;// True to Break On Letter Count, otherwise false

property BreakOnWordCount: boolean;// True to Break On Word Count, otherwise false

property BreakOnAfterString: boolean;// True to insert Break after string, otherwise false

property BreakOnBeforeString: boolean;// True to insert Break before string, otherwise false

property SearchString: string;// The search string

property Count: string;// The Word or Letter count

property CaseSensitive: boolean;// True for a case sensitive search, otherwise false.