

COM+ Delete Action

The COM+ Delete Action allows you to delete registered COM+ applications or COM+ components.

COM+ Delete

General Runtime **Deregister** Partition

Host computer _____
localhost

COM+ application _____

☒ **Name:** _____ ☐ Ignore case

☐ **ID:** _____

☐ Delete application

☐ Do not fail if Application/Package not found

Components to delete _____

☐ Delete all components

Put each component on a new line. Can be CLSIDs, ProgIDs, DLL filenames or DLL pathnames.
COM+ uses 8.3 DOS style names, so if you're using a DLL make sure you use the correct name/path

☐ Fail if any entry does not match any registered components

OK Cancel Help

Host Computer

The name of the computer you want to administrate. You will need Administrator privileges on this computer. Blank is equivalent to localhost.

COM+ Application

You can specify the COM+ Application by its name or ID (GUID.) The action will fail if no application is found.

Check the **"Delete application"** box to remove this application from the server.

Components To Delete

If the **"Delete application"** option is not set, you will need to specify which components to remove from the server. Put each component on a new line in the memo box.

Components can be specified as component names (ProgIDs, as shown in the Component Services Components list), CLSIDs (GUIDs) or DLL filenames or pathnames (partial pathnames are also acceptable.) If DLL names are specified, all components belonging to that DLL will be deleted.

Check the **"Delete all components"** box to remove all components.

Partition

To specify an application on a different COM+ Partition, enter the name or ID (GUID) of the partition on the partition page. If no partition is specified, the action operates on the base partition.