

NuGet Delete Action



The NuGet actions in Continua are a wrapper around the nuget command line. If you're having trouble using any of the NuGet actions, please refer to the [Command Line Reference](#).

The NuGet Delete action provides the ability to remove a package from a NuGet Server.

NuGet Delete

NuGet Delete Action

NuGet Delete Settings Options Environment Comments

Name NuGet Delete [] Required Field

Enabled

Package ID MyPackage ✔
The ID of the NuGet package you want to delete.

Version 1.0 ✔
The version of the NuGet package you want to delete.

API Key 29ab48e3-c3dd-90cd-a944-93c1ad63e892 👁️ ✔
The API key required to delete the package. It's recommended you put this value in a variable. If left blank, then any key specified in the config file will be used. [-ApiKey]

Command Line Version Latest ▼

Using NuGet.Default ▼

Name

A friendly name for this action (will be displayed in the [actions workflow area](#)).

Enabled

Determines if this action will be run within the relevant stage.

Package Id

The Id of the package to remove.

Version

The version of the package to be removed.

API Key

The API Key for the NuGet server which this package is being removed from. [-ApiKey]

Command Line Version

Select the version of the NuGet command line that is installed on the agent. Some other settings and options may be unavailable depending which the command line version is selected.

Using

The Using drop down is populated with any property collector whose namespace matches the pattern defined by the NuGet Delete action. The pattern for this action is `^NuGet.*`

If you create a property collector for this action, make sure you select the **Path Finder Plugin** type and give it a name that will match the pattern above in blue. Example names listed [here](#), search the table's Plugin column for "NuGet Delete".

For more in-depth explanations on property collectors see [Property Collectors](#).

Alternatively, you can select the **Custom** option from the Using drop down list and specify a path in the resulting input field that will be displayed. Please read [Why it's a good idea to use a property collector](#) before using this option.

Settings

NuGet Delete Action

- NuGet Delete
- Settings**
- Options
- Environment
- Comments

Required Field

Source Server 

If you use your own private NuGet feed, specify the server URL here. [-Source]

Configuration File 

A specific NuGet configuration file to use. If omitted, %appdata%\NuGet\nuget.config is used. [-ConfigFile]

   

Source Server

The URL to the NuGet server where this package will be removed from. [-Source]

Configuration File

The NuGet configuration file. If not specified, file %AppData%\NuGet\nuget.config is used. [-ConfigFile]

Options

NuGet Delete Action

NuGet Delete Settings **Options** Environment Comments

Required Field

Verbosity

Force English output
Forces the command line to run using an invariant, English-based culture. [-ForceEnglishOutput]

Timeout (in seconds)

How long to wait for the action to finish running before timing out. Leaving this blank (or zero) will default to 86400 seconds (24 hours).

Treat failure as warning
Tick to continue build on failure marking the action with a warning status.

Ignore warnings

Verbosity

How much information should the command line output? [-Verbosity]

Force English output

Forces the command line to run using an invariant, English-based culture. [-ForceEnglishOutput]

Timeout (in seconds)

How long to wait for the action to finish running before timing out. Leaving this blank (or zero) will default to 86400 seconds (24 hours).

Treat failure as warning

Tick to continue build on failure marking the action with a warning status.

Ignore warnings

If this is ticked, any warnings logged will not mark the action with a warning status.

Environment

NuGet Delete Action

NuGet Delete Settings Options **Environment** Comments

Environment Variables Required Field

variable_name=variable_value ✔

Specify one name & value pair per line.

Log environment variables

Generate system environment variables

Tick this to set new environment variables prefixed with 'ContinuaCI.' for system objects and variables.

Environment Variables

Multiple environment variables can be defined - one per line. These are set before the command line is run.

Log environment variables

If this is ticked, environment variable values are written to the build log.

Generate system environment variables

Tick this checkbox to set up a list of new environment variables prefixed with 'ContinuaCI.' for all current system expression objects and variables.

Mask sensitive variable values in system environment variables

This checkbox is visible only if the 'Generate system environment variables' checkbox is ticked.

If this is ticked, the values of any variables marked as sensitive will be masked with **** when setting system environment variables. Clear this to expose the values.