

XMPP

[XMPP](#) is an open communications standard, supported by public chat services such as Google Talk and [Jabber.org](#). Many companies run internal XMPP-compatible servers. The XMPP publisher allows Continuum CI to send notifications to users or rooms via an XMPP service or server.

XMPP

New Notification Publisher

Publisher

XMPP

Rooms

Options

Required Field

Username

The XMPP username of the message sender

Server

Password

Port

5222

Subscription Types

☒ Users and groups

☒ Rooms

Specify whether subscriptions can be sent only to users and groups, only to rooms, or to both.

Validate

Save

Cancel

Help

Username

Enter the XMPP username to send the message from.

Server

Enter the DNS name of the XMPP server

Server

Enter a password if your XMPP server requires authentication.

Port

Enter the TCP port for a client connections to your XMPP server. The standard XMPP port is 5222, although 5223 is also commonly used for SSL connections. Your server may be configured to use a different port.

Subscription Types

Subscriptions can be set up to send notifications to a specific user, a group of users or an XMPP room. Tick the subscription types that are allowed for this publisher.

Rooms

New Notification Publisher

Publisher

XMPP

Rooms

Options

Required Field

Chat Service Name

conference

Name of the group chat service.

Default Room

Specify the default room name (or room id) for this publisher. This can be overridden when creating a subscription or in user preferences.

Validate

Save

Cancel

Help

Chat Service Name

The name of the chat service which is prefixed to the room name when sending messages to a room.

Default Room

Specify the default room name or id to use when setting up a subscription for this publisher. This can be overridden when setting up a room subscription.

Options

New Notification Publisher

Publisher

XMPP

Rooms

Options

Required Field

Network Host

This may be different to the server name with some XMPP services.
Leave blank to use server name.

Resource Name

Continua CI XMPP Notification Service

☐ Auto-start TLS

☐ Allow untrusted certificates

Validate

Save

Cancel

Help

Network Host

This may be different to the server name with some XMPP services. Leave blank to use server name.

Resource Name

This can be used to differentiate messages from different services using the same username

Auto-start TLS

Tick this if you need to use TLS to securely connect to your XMPP server

Allow untrusted certificates

Tick this to ignore errors connecting to server with self-signed or incorrectly configured SSL certificates.