

Bazaar

Bazaar

New Repository

Repository

Bazaar

Filtering

Downtime

Repository URL

http://bzt-project.example.com/foo.dev/

URL or path to Bazaar repository.

Username

The username to connect to the remote Bazaar repository.

Password

The password to connect to the remote Bazaar repository.

☐ Write changeset details to file

Tick to write changeset details to the file "_CI_ChangesetDetails.xml" after checking out each changeset.

Using

Bazaar.Default

Use the executable found by this property collector.

Validate

Save

Cancel

Help

Repository URL

The URL or Path to your Bazaar repository.

Example:

- S:\bazaar_repo
- \\server\share\bazaar_repo
- http://bzt-project.example.com/foo.dev/

Username

The username required to login to the Bazaar server.

Password

The password required to login to the Bazaar server.

Write changeset details to file

Tick to write changeset details to the file "_CI_ChangesetDetails.xml" after checking out each changeset.

Using

The Using drop down is populated with any property collector whose namespace matches the pattern defined by the Bazaar plugin. The pattern for this action is `^bazaar\..*`

If you create a property collector for this action, make sure you select the **Path Finder Plugin** type and give it a name that will match the pattern above in blue. Example names listed [here](#), search the table's Plugin column for "Bazaar".

For more in-depth explanations on property collectors see [Property Collectors](#).

Alternatively, you can select the **Custom** option from the Using drop down list and specify a path in the resulting input field that will be displayed. Please read [Why it's a good idea to use a property collector](#) before using this option.