

Rake Action



The Rake action in Continua is a wrapper around the rake command line. If you're having trouble using the Rake action, please refer to the [Command Line Reference](#).

The Rake action is a Make-like program implemented in Ruby. Tasks and dependencies are specified in standard Ruby syntax.

Rake

Rake Action

Rake

Options

Environment

Comments

Required Field

Name

Rake []

☒ Enabled

Rake Version

10.1.0

Specify the version of Rake to use (optional).

Rakefile

\$Source.myRepository\$\src\rakefile.rb

The path and filename of your rakefile. [--rakefile]

Working Folder

\$Workspace\$\build

The working folder relative to the workspace folder.

Rake Tasks

build db:migrate

Enter the Rake tasks to execute, separate with a space.

Using

Ruby.Runtime.Default

▼

Validate

Save

Cancel

Help

Name

A friendly name for this action (will be displayed in the [actions workflow area](#)).

Enabled

Determines if this action will be run within the relevant stage.

Rake Version

Specify a version string, e.g. :

`_10.1.0_`

This field is optional. If not specified, the latest rake version installed in the selected ruby environment will be used.

Rake File

Optional - Specify the path and name of the rakefile to use (relative to the build workspace). If not specified, then rake will search the working folder for a file named rakefile.rb or Rakefile.rb. [--rakefile]

Working Folder

Optional - specify the working folder (relative to the build workspace). If not specified, then the build workspace folder is used. This folder should generally be where the rakefile lives, unless the rakefile is specified.

Rake Tasks

Optional - The rake Tasks to execute. If not specified, rake will attempt to execute the default task.

Using

The Ruby Environment to use. Continuum includes default [property collectors](#) to find ruby.exe and jruby.exe.

The Using drop down is populated with any property collector whose namespace matches the pattern defined by the Rake action. The pattern for this action is `^ruby\.runtime\..*`

If you create a property collector for this action, make sure you select the **Path Finder Plugin** type and give it a name that will match the pattern above in blue. Example names listed [here](#), search the table's Plugin column for "Rake".

For more in-depth explanations on property collectors see [Property Collectors](#).

Alternatively, you can select the **Custom** option from the Using drop down list and specify a path in the resulting input field that will be displayed. Please read [Why it's a good idea to use a property collector](#) before using this option.

Options

Rake Action

Rake

Options

Environment

Comments

Required Field

Command Line Options

Extra Rake command line options.

☐ Enable trace

Turn on invoke/execute tracing, enable full backtrace. [--trace=stdout]

☐ Use bundler

Use bundler. [bundle exec -- rake]

Timeout (in seconds)

0

How long to wait for the action to finish running before timing out. Leaving this blank (or zero) will default to 86400 seconds (24 hours).

☐ Treat failure as warning

Tick to continue build on failure marking the action with a warning status.

☐ Ignore warnings

☒ Validate

Command Line Options

Optional - Extra command line arguments to pass to Rake.

Enable Trace

Turn on Invoke/Execute Tracing, enable full backtrace. [--trace=stdout]

Use Bundler

Use the Bundler Gem dependencies manager. When this is enabled, rake will be invoked with bundle exec rake..... [exec -- rake]

Timeout (in seconds)

How long to wait for the action to finish running before timing out. Leaving this blank (or zero) will default to 86400 seconds (24 hours).

Treat failure as warning

Tick to continue build on failure marking the action with a warning status.

Ignore warnings

If this is ticked, any warnings logged will not mark the action with a warning status.

Environment

Rake Action

Rake Options **Environment** Comments

Environment Variables

variable_name=variable_value

Required Field

Specify one name & value pair per line.

☒ Log environment variables

☐ Generate system environment variables

Tick this to set new environment variables prefixed with 'ContinuaCI.' for system objects and variables.

✓ Validate

Save

Cancel

Help

Environment Variables

Multiple environment variables can be defined - one per line. These are set before the command line is run.

Log environment variables

If this is ticked, environment variable values are written to the build log.

Generate system environment variables

Tick this checkbox to set up a list of new environment variables prefixed with 'ContinuaCI.' for all current system expression objects and variables.

Mask sensitive variable values in system environment variables

This checkbox is visible only if the 'Generate system environment variables' checkbox is ticked.

If this is ticked, the values of any variables marked as sensitive will be masked with **** when setting system environment variables. Clear this to expose the values.