

Grunt Action

 The Grunt action in Continua is a wrapper around the Grunt command line. If you're having trouble using the Grunt action, please refer to the [Grunt Command Line Reference](#).

The Grunt action is used to run node.js tasks specified in a [Gruntfile](#).

Grunt

Grunt Action

Grunt

Settings

Options

Environment

Comments

Required Field

Name

Grunt []

☒ Enabled

Gruntfile

\$Source.myRepository\$src\Gruntfile.js

...



The path and file name of your Grunt file. Leave blank to use gruntfile.js in base path. [--gruntfile]

Base Path

\$Workspace\$\build



Tasks

Task1 Task2



Task Directories

\$Workspace\$\build\tasks



Additional directory paths to scan for tasks and extra files. [--tasks]

Using

Grunt.Runtime.Default

▼

 Validate

 Save

 Cancel

 Help

Name

A friendly name for this action (will be displayed in the [actions workflow area](#)).

Enabled

Determines if this action will be run within the relevant stage.

Grunt File

The path and file name of the Grunt file which defines the tasks to run. Leave blank to use the gruntfile.js file located in Base Path. [--gruntfile]

Base Path

An alternate base path. By default, all file paths are relative to the Grunt File. [--base]

Tasks

A space separated list of tasks to run. Leave this black to run all tasks.

Task Directories

Additional directory paths to scan for tasks and task related files. Relative paths will be anchored to the workspace folder. [--tasks]

Using

The Using drop down is populated with any property collector whose namespace matches the pattern defined by the Grunt action. The pattern for this action is `^Grunt.*`

If you create a property collector for this action, make sure you select the **Path Finder Plugin** type and give it a name that will match the pattern above in blue. Example names listed [here](#), search the table's Plugin column for "Grunt".

For more in-depth explanations on property collectors see [Property Collectors](#).

Alternatively, you can select the **Custom** option from the Using drop down list and specify a path in the resulting input field that will be displayed. Please read [Why it's a good idea to use a property collector](#) before using this option.

Settings

Grunt Action

Grunt

Settings

Options

Environment

Comments

NPM Plugins

plugin1 plugin2

NPM-installed grunt plugins to scan for tasks and extra files.

Variables

variable_name=variable_value

Specify one name & value pair per line.

☐ Pre-install Grunt to base path using NPM. [--npm]

Validate

Save

Cancel

Help

NPM Plugins

Names of Grunt plugins to load tasks form. These plugins must be installed locally via NPM, and must be relative to the Gruntfile.

Variables

Additional variables to pass to your Grunt script. Specify one name and value pair per line.

Pre-install Grunt to base path using NPM

Grunt needs to be installed the the base path before the tasks can be run. Tick this to automatically install Grunt before running the Grunt command line. Leave this cleared if you are installing Grunt with a separate preceding NPM action. [--npm]

Run NPM Using

The Using drop down is populated by any property collector properties whose namespace matches the pattern defined by the NPM action. The pattern for this action is `^NPM.*`

If you create a property collector for this pre-install action, make sure you select the **Path Finder Plugin** type and give it a name that will match the pattern above in blue. Example names listed [here](#), search the table's Plugin column for "NPM".

For more in-depth explanations on property collectors see [Property Collectors](#).

Alternatively, you can select the **Custom** option from the Using drop down list and specify a path in the resulting input field that will be displayed. Please read [Why it's a good idea to use a property collector](#) before using this option.

Options

Grunt Action

Grunt

Settings

Options

Environment

Comments

☐

Force your way past warnings [--force]

☒

Log standard output

☐

Verbose logging. [--verbose]

☐

Debug logging [--debug]

Timeout (in seconds)

How long to wait for the action to finish running before timing out. Leaving this blank (or zero) will default to 86400 seconds (24 hours).

☐

Treat failure as warning

Tick to continue build on failure marking the action with a warning status.

☐

Ignore warnings

Required Field

☒ Validate

Force your way past warnings

Tick this to use the --force argument to ignore warnings. [--force]

Log standard output

Tick this to log output from the Grunt command line.

Verbose logging

Tick this to pass the --verbose argument to get more detailed output from the Grunt command line. [--verbose]

Debug logging

Tick this to pass the --debug argument to get more diagnostic output from the Grunt command line. [--debug]

Timeout (in seconds)

How long to wait for the action to finish running before timing out. Leaving this blank (or zero) will default to 86400 seconds (24 hours).

Treat failure as warning

Tick to continue build on failure marking the action with a warning status.

Ignore warnings

If this is ticked, any warnings logged will not mark the action with a warning status.

Environment

Grunt Action

Grunt

Settings

Options

Environment

Comments

Environment Variables

Required Field

variable_name=variable_value

Specify one name & value pair per line.

☒ Log environment variables

☐ Generate system environment variables

Tick this to set new environment variables prefixed with 'ContinuaCI.' for system objects and variables.

Validate

Save

Cancel

Help

Environment Variables

Multiple environment variables can be defined - one per line. These are set before the command line is run.

Log environment variables

If this is ticked, environment variable values are written to the build log.

Generate system environment variables

Tick this checkbox to set up a list of new environment variables prefixed with 'ContinuaCI.' for all current system expression objects and variables.

Mask sensitive variable values in system environment variables

This checkbox is visible only if the 'Generate system environment variables' checkbox is ticked.

If this is ticked, the values of any variables marked as sensitive will be masked with **** when setting system environment variables. Clear this to expose the values.