


Delete Azure Web App Action

 This action is a wrapper for the Azure command line: [az webapp delete](#). If you're having trouble using this action, or any of the Azure actions, please refer to the [Azure command line reference](#).

The Delete Azure Web App action is a [premium action](#) that can be used to delete [web apps](#) on Azure.

See also the [Delete Azure Web App Action](#).

Delete Azure Web App



Delete Azure Web App Action Premium

Delete Azure Web App Authentication Settings Options Environment Comments

Name Delete Web App [] Required Field

Enabled

Working Folder \$Workspace\$ 

Optional working folder for running the executable. Defaults to the workspace folder.

Authentication Actions Login Logout Use Resource Id(s)

Choose whether to log in to Azure before running the command and logout after running the command.

Web App Name 

Name of web app to delete. [--name]

Resource Group 

Name of the resource group the web app is under. [--resource-group]

Using Azure.CLI.Default

Name

A friendly name for this action (will be displayed in the [actions workflow area](#)).

Enabled

Determines if this action will be run within the relevant stage.

Working Folder

The folder where the command line executable is run. This is optional and defaults to the workspace folder.

Authentication Actions

Generally you will need to log in to Azure before running this action and log out afterwards. If you have several Azure actions in a stage, you can avoid repeated logins by unchecking the Login action on all but the first Azure action and unchecking the Logout action on all but the last Azure action. The Authentication tab will be shown if either of these options is ticked.

Use resource ID(s)

If this ticked, the storage account to delete is identified by its resource ID.

Resource ID(s)

This field is visible only if the checkbox 'Use resource ID(s)' is ticked.

List of resource IDs of web apps to delete. One ID per line. [--ids]

Web App Name

The name of the web app to delete. [--name]

Resource Group

The name of the resource group the web app is under. [--resource-group]

Using

The version of the Azure command line to use. It is important that the agent has the correct version of the Azure command line installed for command provided.

The Using drop down is populated with any property collector whose namespace matches the pattern defined by the Create Azure Resource Group action. The pattern for this action is `^Azure.Cli.*`

If you create a property collector for this action, make sure you select the **Path Finder Plugin** type and give it a name that will match the pattern above in blue. Example names listed [here](#), search the table's Plugin column for "Azure Command".

For more in-depth explanations on property collectors see [Property Collectors](#).

Alternatively, you can select the **Custom** option from the Using drop down list and specify a path in the resulting input field that will be displayed. Please read [Why it's a good idea to use a property collector](#) before using this option.

Authentication

The screenshot shows the 'Delete Azure Web App Action' configuration window with the 'Authentication' tab selected. The window has a blue header with the title 'Delete Azure Web App Action' and a 'Premium' label in the top right. Below the header is a navigation bar with tabs: 'Delete Azure Web App', 'Authentication', 'Settings', 'Options', 'Environment', and 'Comments'. The main content area contains a 'Required Field' indicator in the top right. There is a checkbox labeled 'Sign in/out using service principal [login --service-principal]'. Below this are two input fields: 'Username' with a placeholder '[login | logout --username]' and 'Password' with a placeholder 'User's password [login --password]'. The password field has a masked input (dots) and icons for visibility and validation. At the bottom, there are three buttons: 'Validate', 'Save', and 'Cancel', and a 'Help' icon.

Sign in/out using service principal

Tick this to log in or out using a service principal instead of a username and password. An Azure service principal is an identity created for use with applications, hosted services, and automated tools to access Azure resources. This access is restricted by the roles assigned to the service principal, giving you control over which resources can be accessed and at which level. For security reasons, it's always recommended to use service principals with automated tools rather than allowing them to log in with a user identity. [login --service-principal]

[Username / Password Authentication](#)

Username

Enter a username to log into the Azure cloud. This is generally an email address. [login|logout --username]

Password

The password associated with the Azure username. [login --username]

Service Principal Authentication

Delete Azure Web App Action Premium

Delete Azure Web App **Authentication** Settings Options Environment Comments

Sign in/out using service principal [login --service-principal] Required Field

Name or URL 
The URL or name associated with the service principal. [login | logout --username]

Client Secret or Certificate  
Client secret or a pem file with key and public X509 certificate used to create the service principal. [login --password]

Tenant 
The tenant associated with the service principal, as either an .onmicrosoft.com domain or Azure object ID.
[login --tenant]

Use certificate SN issuer [login --use-cert-sn-issuer]

Name or URL

Enter the application name or the URL associated with the service principal. [login --service-principal --username]

Client Secret or Certificate

Enter the service principal password, or the path to a X509 certificate used to create the service principal in PEM format. [login --service-principal --password]

Tenant

Enter the tenant associated with the service principal, as either an [.onmicrosoft.com](https://onmicrosoft.com) domain or Azure object ID. [login --service-principal --tenant]

Use certificate SN issuer

Tick to support automatic certificate rollovers with service principals configured with Subject Name and Issuer Authentication. [login --use-cert-sn-issuer]

Settings

Delete Azure Web App Action Premium

Delete Azure Web App Authentication **Settings** Options Environment Comments

Required Field

Slot 

The name of the slot. Leave empty to default to the production slot. [--slot]

Keep DNS registration. [--keep-dns-registration]

Keep empty app service plan. [--keep-empty-plan]

Keep app metrics. [--keep-metrics]

Subscription 

Name or ID of the subscription. Leave blank for default. [--subscription]

Slot

The name of the slot. Leave empty to default to the production slot. [--slot]

Keep DNS registration

If this is ticked, the DNS registration associated with the web app is kept. [--keep-dns-registration]

Keep empty app service plan

If this is ticked, any empty app service plan is kept. [--keep-empty-plan]

Keep app metrics

If this is ticked, related app metrics are kept. [--keep-metrics]

Subscription

The name or ID of the subscription to use. If omitted the default subscription for your environment will be used. [--subscription]

Options

Delete Azure Web App Action Premium

Delete Azure Web App Authentication Settings **Options** Environment Comments

Required Field

Log Level

Timeout (in seconds)
How long to wait for the action to finish running before timing out. Leaving this blank (or zero) will default to 86400 seconds (24 hours).

No Response Timeout (in seconds)
How many seconds to wait for the Azure commands to respond with output before timing out. Leave zero to wait until the main timeout.

Treat failure as warning
Tick to continue build on failure marking the action with a warning status.

Ignore warnings

Log Level

The amount of information detail to display in the build log.

Timeout (in seconds)

How long to wait for the action to finish running before timing out. Leaving this blank (or zero) will default to 86400 seconds (24 hours).

No Response Timeout (in seconds)

How many seconds to wait for the Azure commands to respond with output before timing out. Leave zero to wait until the main timeout.

Treat failure as warning

Tick to continue build on failure marking the action with a warning status.

Ignore warnings

If this is ticked, any warnings logged will not mark the action with a warning status.

Environment

Delete Azure Web App Action Premium

Delete Azure Web App Authentication Settings Options **Environment** Comments

Environment Variables Required Field

variable_name=variable_value

Specify one name & value pair per line.

Log environment variables

Generate system environment variables

Tick this to set new environment variables prefixed with 'ContinuaCI.' for system objects and variables.

Environment Variables

Multiple environment variables can be defined - one per line. These are set before the command line is run.

Log environment variables

If this is ticked, environment variable values are written to the build log.

Generate system environment variables

Tick this checkbox to set up a list of new environment variables prefixed with 'ContinuaCI.' for all current system expression objects and variables.

Mask sensitive variable values in system environment variables

This checkbox is visible only if the 'Generate system environment variables' checkbox is ticked.

If this is ticked, the values of any variables marked as sensitive will be masked with **** when setting system environment variables. Clear this to expose the values.