

# Pip Wheel Action



The Pip actions in Continuum is a wrapper around the pip.exe command line. If you're having trouble using the Pip actions, please refer to the [Command Line Reference](#).

Pip Wheel action is used to build Wheel archives for your requirements and dependencies.

## Pip Wheel

**Pip Wheel Action**

Pip Wheel

Settings

Connection

Installation

Package Index

Extra Arguments

Options

Environment

Comments

Required Field

Name

Pip Wheel []

☒ Enabled

Working Folder

The working directory for the pip command line. Leave blank to default to the workspace folder.

Package To Build Wheel For

MyPackage

The name of the Python package, the URL of the VCS project, a local project directory, or the path/URL of a local/remote package archive to build the wheel for. Leave blank or '.' to search in working folder.

☐ Install the project in editable mode. [--editable]

Requirements File(s)

requirementsfile.txt  
requirementsfile2.txt

Install packages from the given requirements files. One file path per line. [--requirement]

Output Directory

MyPackage

Path to the directory where the wheel will be built. Defaults to the working folder. [--wheel]

☒ Use command line executable in virtual environment scripts folder if it exists.

Using

Pip.Default ▼

Validate

Save

Cancel

Help

### Working Folder

The working directory for the pip command line. Leave blank to default to the workspace folder.

### Package To Build Wheel For

The name of the Python package, the URL of the VCS project, a local project directory, or the path/URL of a local/remote package archive to build the wheel for. Leave blank or '.' to search in working folder.

Note that if installing a VCS project in editable mode it must be in the form: vcs+[protocol://repo\\_url/#egg=pkg&subdirectory=pkg\\_dir](#). (e.g git+[http://git.example.com/MyProject#egg=MyProject](#)). For more information please refer to [Pip Install VCS Support](#).

### Install the project in editable mode

If this is ticked, the project is installed in editable mode.

### Requirements File(s)

Install packages from the given requirements files. One file path per line. [--requirement]

### Output Directory

Visible only if the checkbox 'Install the project in editable mode' is NOT ticked.

Path to the directory where the wheel will be built. Defaults to the working folder. [--wheel]

## Source Directory

Visible only if the checkbox 'Install the project in editable mode' is ticked.

The directory to check out editable projects into. The default when running under a virtual environment is "<venv path>\src". The default for global installs is "<current dir>\src". [--src]

## Use command line executable in virtual environment scripts folder if it exists.

If this is ticked and exists, the pip executable in the virtual environment scripts folder will be used instead.

## Using

The Using drop down is populated by any property collector properties whose namespace matches the pattern defined by the Pip Wheel action. The pattern for this action is `^Pip\.*`. The default property collector searches the environment path for "pip.exe".

If you create a property collector for this action, make sure you select the **Path Finder Plugin** type and give it a name that will match the pattern above in blue. Example names listed [here](#), search the table's Plugin column for "**Pip**".

For more in-depth explanations on property collectors see [Property Collectors](#).

Alternatively, you can select the **Custom** option from the Using drop down list and specify a path in the resulting input field that will be displayed. Please read [Why it's a good idea to use a property collector](#) before using this option.

## Settings

Pip Wheel Action

Pip Wheel

Settings

Connection

Installation

Package Index

Extra Arguments

Options

Environment

Comments

Non-Binary Packages

Default

Specify any packages for which binary packages should not be used. [--no-binary]

Binary Only Packages

Default

Specify any packages for which only binary packages should not be used. [--only-binary]

Constraints File(s)

constraintsfile.txt

Constrain versions using the given constraints files. One file path per line. [--constraint]

☐

Prefer older binary packages over newer source packages. [--prefer-binary]

Validate

Save

Cancel

Help

### Non-Binary Packages

Specify any packages for which binary packages should not be used. [--no-binary]

- **All** - Disable all binary packages.
- **None** - Empty the set of binary packages to be disabled.
- **Custom List** - The custom set of binary packages to be disabled.

Note that some packages are tricky to compile and may fail to install when this option is used on them.

### Non-Binary Package Names

Visible only if the option '**Custom List**' is selected.

The names of the non-binary packages. One per line.

### Binary Only Packages

Specify any packages for which only binary packages should not be used. [--only-binary]

- **All** - Disable all source packages.
- **None** - Empty the set of source packages to be disabled.
- **Custom List** - The custom set of source packages to be disabled.

Note that packages without binary distributions will fail to install when this option is used on them.

### Binary Only Package Names

Visible only if the option '**Custom List**' is selected.

The names of the non-binary packages. One per line.

### Constraints File(s)

Constrain versions using the given constraints files. One file path per line. [--constraint]

### Prefer older binary packages over newer source packages.

If this is ticked, older binary packages will be used instead of newer source packages. [--prefer-binary]

## Connection

Pip Wheel Action

Pip Wheel

Settings

Connection

Installation

Package Index

Extra Arguments

Options

Environment

Comments

Required Field

Proxy

Specify a proxy in the form [user:passwd@]proxy.server:port. It is recommended to use a password type variable to store the password. [--proxy]

Trusted Host

Mark this host as trusted even if it does not have valid or any HTTPS. [--trusted-host]

CA Certificate

Path to the alternate CA bundle. [--cert]

Client Certificate

Path to the SSL client certificate. A single file containing the private key and the certificate in PEM format. [--client-cert]

Timeout

Set the socket timeout in seconds. Leave zero to default to 15 seconds. [--timeout]

Retries

Maximum number of retries each connection should attempt. Leave zero to default to 5 times. [--retries]

Validate

Save

Cancel

Help

## Proxy

Specify a proxy in the form [user:passwd@]proxy.server:port. It is recommended to use a password type variable to store the password. [--proxy]

## Trusted Host

Mark this host as trusted even if it does not have valid or any HTTPS. [--trusted-host]

## CA Certificate

The path to the alternate CA bundle. [--cert]

## Client Certificate

The path to the SSL client certificate. A single file containing the private key and the certificate in PEM format. [--client-cert]

## Timeout

Set the socket timeout in seconds. Leave zero to default to 15 seconds. [--timeout]

## Retires

Maximum number of retries each connection should attempt. Leave zero to default to 5 times. [--retries]

## Installation

Pip Wheel Action

Pip Wheel

Settings

Connection

Installation

Package Index

Extra Arguments

Options

Environment

Comments

Build

MyPackage

Directory to unpack packages into and build in. [--build]

Source Distribution

Default

Select whether to use PEP 517 for building source distributions or force legacy behaviour. [--use-pep517 | --no-use-pep517]

☐ Don't install package dependencies. [--no-deps]

☐ Disable isolation when building a modern source distribution. [--no-build-isolation]  
 Build dependencies specified by PEP 518 must already be installed if this option is used.

☐ Don't clean up build directories. [--no-clean]

☐ Ignore the Requires-Python information. [--ignore-requires-python]

☐ Require a hash to check each requirement against, for repeatable installs. This option is implied when any package in a requirements file has a --hash option. [--require-hashes]

☐ Include pre-release and development versions. By default, pip only finds stable versions. [--pre]

Validate

Save

Cancel

Help

## Build

Directory to unpack packages into and build in. [--build]

## Source Distribution

Select whether to use PEP 517 for building source distributions or force legacy behaviour. [--use-pep517 | --no-use-pep517]

### Don't install package dependencies.

If this is ticked, package dependencies are not installed. [--no-deps]

### Disable isolation when building a modern source distribution.

If this is ticked, isolation is disabled when building a modern source distribution. [--no-build-isolation]

### Don't clean up build directories.

If this is ticked, build directories are not cleaned. [--no-clean]

### Ignore the Requires-Python information.

If this ticked, the Requires-Python information is ignored. [--ignore-requires-python]

### Require a hash to check against each requirement for repeatable installs. This is implied when any package in a requirements file has a --hash option.

If this is ticked, a hash is required to check against each requirement for repeatable installs. This is implied when any package in a requirements file has a --hash option. [--require-hashes]

### Include pre-release and development versions. By default, pip only finds stable versions.

If this is ticked, pip will also find pre-release and development versions. By default, pip only finds stable versions. [--pre]

## Package Index

**Pip Wheel Action**

Pip Wheel

Settings

Connection

Installation

**Package Index**

Extra Arguments

Options

Environment

Comments

☐ No index. [--no-index]

Index URL

https://pypi.org/simple

Base URL of Python Package Index. Default is https://pypi.org/simple. This should point to a repository compliant with PEP 503 (the simple repository API) or a local directory laid out in the same format. [--index-url]

Extra Index URLs

https://pypi.org/simple

Extra URLs of package indexes to use in addition to --index-url. Should follow the same rules as --index-url. One per line. [--extra-index-url]

Validate

Save

Cancel

Help

### No Index

If this is ticked, the package index is ignored. Only look at find links URLs instead.

### Index URL

Visible only if the checkbox '**No Index**' is NOT ticked.

The base URL of Python Package Index. Default is <https://pypi.org/simple>. This should point to a repository compliant with PEP 503 (the simple repository API) or a local directory laid out in the same format. [--index-url]

### Extra Index URLs

Visible only if the checkbox '**No Index**' is NOT ticked.

The extra URLs of package indexes to use in addition to --index-url. Should follow the same rules as --index-url. [--extra-index-url]

### Find Links

Visible only if the checkbox '**No Index**' is ticked.

If a URL or path to a HTML file is specified, then it is parsed for links to archives. If a local path or file:// URL that's a directory is specified, then the directory listing will be searched for archives. [--find-links]

## Extra Arguments

Pip Wheel Action

Pip Wheel

Settings

Connection

Installation

Package Index

Extra Arguments

Options

Environment

Comments

Global Options

Required Field

--no-user-cfg

Extra global options to be supplied to the setup.py call before the install command. One per line. [--global-option]

Validate

Save

Cancel

Help

## Global Options

Extra global options to be supplied to the setup.py call before the install command. One per line. [--global-option]

## Options

Pip Wheel Action

Pip Wheel

Settings

Connection

Installation

Package Index

Extra Arguments

Options

Environment

Comments

Required Field

Verbosity

Normal

Specifies the amount of information to display in the build log.

Log File

Logfile.txt

The path to a verbose appending log file. [--log]

☐

Disable the cache. [--no-cache-dir]

Cache Directory

CacheDir

The path to a directory to store the cache data. [--cache-dir]

☐

Run pip in an isolated mode, ignoring environment variables and user configuration. [--isolated]

Exists Action

Ignore

Specify what to do if path already exists. [--exists-action]

Timeout (in seconds)

0

How long to wait for the action to finish running before timing out. Leaving this blank (or zero) will default to 86400 seconds (24 hours).

☐

Treat failure as warning

Tick to continue build on failure marking the action with a warning status.

☐

Ignore warnings

Validate

Save

Cancel

Help

## Verbosity

The amount of information detail to display in the build log. [-qqq | -qq | -q | -v]

## Log File

The path to a verbose appending log file. [--log]

## Disable the cache.

If this is ticked, the cache is disabled. [--no-cache-dir]

## Cache Directory

Visible only if the checkbox 'Disable the cache' is NOT ticked.

The path to a directory to store the cache data. [--cache-dir]

## Run pip in an isolated mode, ignoring environment variables and user configuration.

If this ticked, pip is run in an isolated mode, ignoring environment variables and user configuration. [--isolated]

## Exists Action

Specify what to do if path already exists. [--exists-action]

- **Switch** - Only relevant to VCS checkout. Attempt to switch the checkout to the appropriate URL and/or revision.
- **Ignore** - Abort current operation (e.g. don't copy file, don't create archive, don't modify a checkout).
- **Wipe** - Delete the file or VCS checkout before trying to create, download, or checkout a new one.
- **Backup** - Rename the file or checkout to {name}-{ ' .bak ' \* n }, where n is some number of .bak extensions, such that the file didn't exist at some point. So the most recent backup will be the one with the largest number after .bak.
- **Abort** - Abort pip and return non-zero exit status.

## Timeout (in seconds)



How many seconds to wait for the action to finish before timing out. The default is 86400 seconds (24 hours).

### Treat failure as warning

Tick to continue build on failure marking the action with a warning status.

### Ignore warnings

If this is ticked, any warnings logged will not mark the action with a warning status.

## Environment

**Pip Wheel Action**

Pip Wheel

Settings

Connection

Installation

Package Index

Extra Arguments

Options

**Environment**

Comments

Environment Variables

variable\_name=variable\_value

Required Field

Specify one name & value pair per line.

☒ Log environment variables

☐ Generate system environment variables

Tick this to set new environment variables prefixed with 'ContinuaCI.' for system objects and variables.

Validate

Save

Cancel

Help

### Environment Variables

Multiple environment variables can be defined - one per line. These are set before the command line is run.

### Log environment variables

If this is ticked, environment variable values are written to the build log.

### Generate system environment variables

Tick this checkbox to set up a list of new environment variables prefixed with 'ContinuaCI.' for all current system expression objects and variables.

### Mask sensitive variable values in system environment variables

This checkbox is visible only if the 'Generate system environment variables' checkbox is ticked.

If this is ticked, the values of any variables marked as sensitive will be masked with \*\*\*\* when setting system environment variables. Clear this to expose the values.

