

Perforce

Perforce

New Repository

Repository

Perforce

Credentials

Options

Filtering

Downtime

Required Field

Server

MyPerforceServer:1666

Server name and port of Perforce server. You can optionally include the protocol (eg. ssl:server:port).

☒ Using a recent Perforce version
Using Perforce version 2012.1 or a more recent version.

Client Views

//depot/... //workspace/...

Mappings between files in the depot and files in client workspaces. These must include the word 'workspace' which will be translated as the location of client workspace.

Using

Perforce.Default

Use the executable found by this property collector.

Validate

Save

Cancel

Help

Server

The hostname and port of the Perforce server. The hostname and port should be separated by a colon :. The format is [protocol]:[hostname]:[port].

Examples

```
ssl:perforce_host:1666
```

```
perforce_host:1666
```

Note: The protocol is optional.

Using a recent Perforce version

Using Perforce version 2012.1 or a more recent version.

Client Views

The list of mappings between files in the depot and files in client workspaces. These must include the word 'workspace' which will be translated as the location of client workspace. Please note that the order of the mappings is important; a later mapping overrides an earlier mapping.

Examples

```
//depot/... //workspace/...

//depot/dir/... //workspace/dir2/...


//depot/main/*.js //workspace/main/scripts/*.js

-//depot/dir/exclude/... //workspace/dir/exclude/...

//depot/v1/... "//workspace/version 1/..."
```

Using

The Using drop down is populated with any property collector whose namespace matches the pattern defined by the Perforce plugin. The pattern for this action is `^perforce\..*`

If you create a property collector for this action, make sure you select the **Path Finder Plugin** type and give it a name that will match the pattern above in blue. Example names listed [here](#), search the table's Plugin column for "Perforce".

For more in-depth explanations on property collectors see [Property Collectors](#).

Alternatively, you can select the **Custom** option from the Using drop down list and specify a path in the resulting input field that will be displayed. Please read [Why it's a good idea to use a property collector](#) before using this option.

Credentials

New Repository

Repository

Perforce

Credentials

Options

Filtering

Downtime

Required Field

Username

The username to connect to the Perforce server.

Password

The password to connect to the Perforce server.

☐ Use tickets

Use ticket based authentication.

Validate

Save

Cancel

Help

Username

The username to use when managing the Perforce repository.

Password

The corresponding password to the username used to manage the repository.

Use Tickets

Tick to use ticket based authentication

Options

New Repository

Repository

Perforce

Credentials

Options

Filtering

Downtime

Required Field

Character Set


utf8

The character set to use when connecting to the server. (-C)


Command CharSet


utf8


A non-UTF16/32 character set to use for the command line when using a UTF16/32 on the server. (-Q)


☐ Write changeset details to file 

Tick to write changeset details to the file "_CI_ChangesetDetails.xml" after checking out each changeset.

 Validate

 Save

 Cancel

 Help

Character Set

The character set to use when connecting to the server. (-C)

Command CharSet

A non-UTF16/32 character set to use for the command line when using a UTF16/32 on the server. (-Q)

Write changeset details to file

Tick to write changeset details to the file "_CI_ChangesetDetails.xml" after checking out each changeset.